



VERSACOOLER™ BI-LEVEL CONTACTLESS DRINKING FOUNTAIN,
REFRIGERATED & ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PG8FEBFSLTT-FVF

Suggested Specification

Model PG8FEBFSLTT-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include the VersaFiller® with contactless activation and laminar flow; each fountain shall have independent activation using contactless infrared sensor to activate the flow of water. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.



- Features:**
- Universal design: high right or high left
 - Built-in 100 micron strainer stops particles before they enter the waterway
 - Waterways are lead-free in materials & construction
 - High efficiency cooling system
 - Stainless steel top and heavy duty galvanized steel frame
 - Contactless activation bottle filler with programmable auto shut off
 - Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive
 - Includes integral self-scouring waste drain
 - External access to stream height adjustment on lower Versacooler fountain
 - External access to thermostat with tool activated OFF position
 - Filters located in top bottle filler for easy filter replacement with Tilt 'N Tether
 - Built-in filter monitor and bottle counter
 - Logos permanently formed into the alcove and stainless steel wrapper
 - LED lighted alcove

Filtration System: OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.

Power: 115 Volts, 60 Hz

Activation By: Contactless Sensor on Bottle Filler;
Contactless Activation on Left Fountain/Manual
Activation on Right Fountain

Mounting Type: Wall Mounted

Chilling Option: 8.0 gph*

Full Load Amps 5.0 amps

Rated Watts 500

Approx. Net Weight 82 lbs

Installation Location: Indoor

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____

Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

Finishes

- Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



VERSACOOLER™ BI-LEVEL CONTACTLESS DRINKING FOUNTAIN,
REFRIGERATED & ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PG8FEBFSLTT-FVF

Accessories



OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



One piece chrome plated brass bubbler

OASIS Item #036700-001



[View all filters and accessories](#)

