



Suggested Specification

BI-LEVEL OUTDOOR VANDAL RESISTANT FOUNTAIN, REFRIGERATED & OUTDOOR VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER

MODEL PGVD8SVDBFSL

Model PGVD8SVDBFSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include a vandal resistant bottle filler with vandal resistant electro-mechanical push button activation and laminar flow, each fountain shall have a single vandal resistant push button to activate the manual flow of water for the cooler. All bottle filler exterior cabinet and drip tray shall be 18 gauge stainless steel. Key bottle filler components contain Freshshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Vandal Resistant water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. One-piece vandal resistant metal bubbler keyed into place to prevent vandalism. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:

- Universal design: high right or high left
Built-in 100 micron strainer stops particles before they enter the waterway
Waterways are lead-free in materials & construction
Vandal resistant metal water saver bubbler
Vandal resistant manual solenoid activation push button on the bottle filler and vandal resistant push button on fountains
Vandal resistant fasteners on bottle filler and fountains
Galvanized steel louver and bottom screens
Stainless steel top and heavy duty galvanized steel frame
High efficiency cooling system
Includes integral self-scouring waste drain
Ample space within the bottle filler cabinet to add filtration
Access through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether
External access to thermostat with tool activated OFF position
Built-in filter monitor and bottle counter
Logos permanently formed into stainless steel wrapper

Table with specifications: Filtration, Power, Activation By, Mounting Type, Chilling Option, Full Load Amps, Rated Watts, Approx. Net Weight, Installation Location.

MODEL: QTY:
PROJECT:
CONTACT:
NOTES:
APPROVAL: DATE:



Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
Shipped with complete instructions and wall mounting bracket
Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

*Ensure filters are certified for outdoor use.

**Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



Specifications subject to change without notice



BI-LEVEL OUTDOOR VANDAL RESISTANT FOUNTAIN, REFRIGERATED &
OUTDOOR VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER
MODEL PGVD8SVDBFSL

Accessories



Cane apron, Stainless Steel

OASIS Item #035174-003

- ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.



[View all filters and accessories](#)



BI-LEVEL OUTDOOR VANDAL RESISTANT FOUNTAIN, REFRIGERATED &
 OUTDOOR VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER
MODEL PGVD8SVDBFSL

NOTES:

1. TRAP, STOP VALVE AND ELECTRICAL OUTLET NOT FURNISHED.
2. ALLOW 4 INCHES (102MM) MIN. PER SIDE FOR VENTILATION.
- *3. RECOMMENDED ADULT BARRIER FREE HEIGHT INSTALLATION SHOWN. REDUCE HEIGHT BY 3 INCHES FOR INSTALLATIONS USED PRIMARILY BY CHILDREN AGES 12 AND YOUNGER. UNIT SHALL ALSO HAVE A MINIMUM CLEAR FLOOR SPACE 307(60) BY 481(220). ADJUST VERTICAL DIMENSIONS AS REQ'D TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
4. 115V GROUND NORTH AMERICAN DUPLEX RECEPTICAL REQUIRED. THIS DRINKING WATER COOLER IS INTENDED TO BE CONNECTED TO A 20A MINIMUM GROUND FAULT CIRCUIT INTERRUPTING (GFCI) DEVICE TO MEET ALL REQUIREMENTS.
5. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS () ARE IN MILLIMETERS.

