



**We Know Water.**

## VERSAFILLER® RETROFIT KIT

### • PWSBF

#### Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWSBF bottle filler has independent push button manual activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key plastic components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

<b>Features:</b>	<ul style="list-style-type: none"> <li>Waterways are lead-free in materials &amp; construction</li> <li>Heavy duty galvanized steel frame</li> <li>Surface mount frame assembly</li> <li>VersaFiller has independent mechanical activation</li> <li>Ample space within the bottle filler cabinet to add filtration, including all OASIS filters</li> <li>Access through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether</li> <li>Logos permanently formed into the alcove and stainless steel wrapper</li> </ul>
<b>Filtration:</b>	Utilizes existing filtration if applicable. Option to add filtration to top of bottle filler
<b>Chilling Options:</b>	Utilizes existing refrigeration system if applicable
<b>Activation By:</b>	Independent Manual Activation on Bottle Filler
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	Utilizes existing refrigeration system if applicable
<b>Approx. Net Weight:</b>	16 lbs.
<b>Installation Location:</b>	Indoor

The PWSBF VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed.

**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



#### Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

#### Finishes

- VersaFiller cabinet finish is stainless steel

#### Options

- Elkay Adapter Gasket 041114-001 - Required
- OASIS Versafilter III Kit 041253-001

#### Limited 1-Year Warranty

(Continental limits of the United States and Canada)  
One year on components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

#### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

#### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



Specifications subject to change without notice

