



SURFACE MOUNT VERSAFILLER® ELECTRONIC BOTTLE FILLER, NON-REFRIGERATED, VERSAFILTER III FILTER

MODEL PWSMFEBF-FVF

Suggested Specification

PWSMFEBF-FVF bottle filler shall include contactless activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall be surface mount in design. Unit shall include filter monitor and bottle counter. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials & construction
- Low profile design saves space
- Heavy duty galvanized steel frame
- Contactless activation bottle filler with programmable auto shut off
- Filter located in bottle filler
- Built-in filter monitor and bottle counter
- Logos permanently formed into the alcove and stainless steel wrapper
- LED lighted alcove
- Surface mount frame assembly

Filtration System:

OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.

Power:

115 Volts, 60 Hz

Activation By:

Contactless Sensor

Mounting Type:

Wall Mounted

Chilling Option:

Non-refrigerated

Full Load Amps

0.2 amps

Rated Watts

11

Approx. Net Weight

18 lbs

Installation Location:

Indoor

Note: Chiller units sold for these models must be remotely located, as they do not fit into the housing of the unit, or inside the wall cavity of a typical stud wall.



Ships in one box.

Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Surface mount frame included, but water supply and drain required
- Shipped with complete instructions and wall mounting brackets.

Finishes

- Standard cabinet finish: Stainless steel

Limited 1-Year Warranty

(Continental limits of the United States and Canada)

One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



SURFACE MOUNT VERSAFILLER® ELECTRONIC BOTTLE FILLER,
NON-REFRIGERATED, VERSAFILTER III FILTER
MODEL PWSMFEBF-FVF

Accessories



OASIS VersaFilter III Replacement Cartridge

OASIS Item # 041145-001

- Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



Remote Chiller

R5 Chiller, OASIS Item # 502990

R8 Chiller, OASIS Item # 502991

R12 Chiller, OASIS Item # 502993



[View all filters and accessories](#)



SURFACE MOUNT VERSAFILLER® ELECTRONIC BOTTLE FILLER,
NON-REFRIGERATED, VERSAFILTER III FILTER

MODEL PWSMFEBF-FVF

