



We Know Water.

# CONTACTLESS SURFACE MOUNT VERSAFILLER® WITH VERSAFILTER™ II

## • PWSMFEBF

### Suggested Specification

VersaFiller alcove and cabinet shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall be surface mount in design. Unit shall include filter monitor and bottle counter. Shall comply with ANSI 117.1 and ADA. Units also meet guidelines for children's accessibility providing the floor to bubbler orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

<b>Features:</b>	<ul style="list-style-type: none"> <li>Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>Waterways are lead-free in materials &amp; construction</li> <li>Low profile design saves space</li> <li>Heavy duty galvanized steel frame</li> <li>Contactless activation bottle filler with programmable auto shut off</li> <li>VersaFilter III located in bottle filler</li> <li>Built-in filter monitor and bottle counter</li> <li>Logos permanently formed into the alcove and stainless steel wrapper</li> <li>LED lighted alcove</li> <li>Surface mount frame assembly</li> </ul>
<b>Filtration:</b>	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons
<b>Power:</b>	115 Volts, 60 Hz
<b>Activation By:</b>	Contactless Sensor
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	Non-refrigerated
<b>Full Load Amps:</b>	0.2
<b>Rated Watts:</b>	11
<b>Approx. Net Weight:</b>	18 lbs.
<b>Installation Location:</b>	Indoor

Note: Chiller units sold for these models must be remotely located, as they do not fit into the housing of the unit, or inside the wall cavity of a typical stud wall.



### Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Surface mount frame included, but water supply and drain required
- Shipped with complete instructions and wall mounting brackets.

### Finishes

- VersaFiller cabinet finish is stainless steel

### Options

- Remote Chiller

### Limited 1-Year Warranty

(Continental limits of the United States and Canada)  
One year on components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice

# OASIS® SURFACE MOUNT VERSAFILLER® WITH VERSAFILTER™ III

